





Select the unit online in a few clicks and get full technical data at blaubergselector.com

READING THE MODEL CODE

Core type Installation Control panel Cooling coil type CF: counterflow P: ceiling CDX: DX-coil S30: th-Tune R: rotary H: double-deck CW: Water coil **S32**: pGDe _: No cooling V: vertical BLAUAIR BL02 CFH 1500-HE-CDX-L-S30 Casing size Airflow [m³/h] Service side Heater type BL01, BL02, 800, 1500, 2500, HE: Electric L: left BL03, BL07, 3500, 5000, HW: Water **R**: Right _: No heater BL09 6000, 9000



Blauberg North America 1501 Veterans Memorial Pkwy E, Ste. 202, Lafayette, IN 47905 tel.: 765 780 7139

> info@blauberg-na.com blauberg-na.com

Technical changes reserved. Illustrations and texts are non-binding.

07/2024











BLAUAIR CFH


Floor mounted heat recovery units



BLAUAIR CFH

Premium range of floor mounted heat recovery units for commercial applications.

The unit is available in seven sizes with rated air flow 470–5295 CFM, with heaters and cooling coils.



EC

FANS

Fans with EC motors. Impellers with backward-curved blades.

Low power consumption at any speed, low noise and stable operation in any climate.

CONTROLS

Integrated plug-and-play controls based on Carel kVent controller.

CAREL

Easy connectivity via Web interface by Ethernet cable. **Modbus** and **Bacnet protocols.**



USER PANELS

S30 th-Tune: simple control panel ensures basic setting options with user-friendly interface.



S32 pGDe: extended control panel for full functionality engineering adjustment.



FRAMELESS/WITH FRAME DESIGN

Casing panels made of zinc-aluminum coated steel with a 1 5/8" mineral wool heat- and sound-instulating layer. Corrosion class C4 according to ISO 12944: class C4. Each model available in left or right versions.

HEAT EXCHANGER

High-efficient **Eurovent certified** counterflow heat exchanger made of profiled plastic plates, packed with elastic heat-resistant sealant. Stainless steel drain pan on both supply and exhaust sides.





ErP '18 ready



BYPASS AND DAMPERS

Automatic heat exchanger bypass damper with a **Belimo actuator** provides active frost protection, free-heating and free-cooling functions. Integrated automatic external dampers with Belimo drives.



FILTERS

Panel MERV13 class filters on both supply and exhaust.