








Select the unit online in a few clicks and get full technical data at blaubergselector.com

READING THE MODEL CODE



Blauberg North America 1501 Veterans Memorial Pkwy E, Ste. 202, Lafayette, IN 47905 tel.: 765 780 7139

> info@blauberg-na.com blauberg-na.com

Technical changes reserved.

Illustrations and texts are non-binding.

07/2024










BLAUAIR CFV

Premium range of floor mounted heat recovery units for commercial applications.

The unit is available in five sizes with rated air flow 470-3530 CFM, with heaters and cooling coils.









FANS

Fans with EC motors. Impellers with backward-curved blades.

Low power consumption at any speed, low noise and stable operation in any climate.

CONTROLS

Integrated plug-and-play controls based on Carel kVent controller.



Easy connectivity via Web interface by Ethernet cable. **Modbus** and Bacnet protocols.





USER PANELS

S30 th-Tune: simple control panel ensures basic setting options with user-friendly interface.



S32 pGDe: extended control panel for full functionality engineering adjustment.



FRAMELESS CASING SYSTEM

Casing panels made of zinc-aluminum coated steel with a 15/8" mineral wool heat- and sound-instulating layer. Corrosion class C4 according to ISO 12944: class C4. Each model available in left or right versions.

HEAT EXCHANGER

High-efficient Eurovent certified counterflow heat exchanger made of profiled aluminum plates, packed with elastic heat-resistant sealant. Stainless steel drain pan on both supply and exhaust sides.

BYPASS AND DAMPERS

Automatic heat exchanger bypass damper with a Belimo actuator provides active frost protection, free-heating and free-cooling functions. Integrated automatic external dampers with Belimo



FILTERS

Panel MERV13 class filters on both supply and exhaust.