BLAUBERG/NA

Ultra 250

Centrifugal Fan

Description

- The Ultra fans are centrifugal exhaust fans for intermittent or continuous ventilation of bathrooms, showers, kitchens and other utility spaces.
 For high-resistant ventilation systems.
- Compatible with \emptyset 6" air ducts.



Benefits

- Low noise level
- The maintenance-free motor bearings.
- The centrifugal impeller has forward-curved blades.

Specification

- Voltage: 120 V, 60 Hz
- Motor: AC motor
- Power consumption: 62 W • Sones: 1.5
- Airflow capacity: up to 242 CFM
- Duct compatibility: Ø 6"
- IPX4 protection


Performance


Model	Duct Dia	Watts*	Amps*	RPM*	Sones*	CFM vs. Static Pressure in.W.G.						Max. Ps	Volts / Hz	
						0"	0.1"	0.2"	0.25"	0.3"	0.4"	0.5"	Max. F3	VOICS / 112
Ultra 250 (120V/60Hz)	6"	62	0.56	1085	1,5	242	240	204	194	182	158	134	0.82	120 / 60

* Indicated at 0.1 in.W.G.

Overall dimensions [in (mm)]

Model	a	b	c	Ø d
Ultra 250 Square	7 3/4 (198)	1 1/2 (38)	13 (330)	5 7/8 (148)





MODEL	QUANTITY	COMMENTS	PROJECT
			location:
			architect:
			engineer:
			contractor:
			submitted by: