

BlauAIR CFP 2500

Ceiling mounted heat recovery units

- Sound pressure level LpA at 3 m: 39
- Heat exchanger type: Counter flow
- Sound insulation
- Motor type: EC
- Casing material: Aluzinc steel



| | Unit of measurement | BlauAIR CFP 2500 |
|--|---------------------|------------------|
| Speed | - | 1 |
| Phases | - | 1 |
| Minimum supply voltage | V | 200 |
| Maximum supply voltage | V | 240 |
| Power supply frequency | Hz | 50/60 |
| Rated power | W | 2x740 |
| Maximum airflow | m ³ /h | |
| Maximum performance @0.1" | CFM | 1470 |
| Sound pressure level LpA at 3 m | dB(A) | 39 |
| Heat exchanger type | - | Counter flow |
| Heat exchanger material | - | Aluminum |
| Weight | kg | 0 |
| Transported air temperature (max) | °C | 122 |
| Transported air temperature (min) | °C | -31 |
| Ambient air temperature min | °C | 0 |
| Ambient air temperature max | °C | 0 |
| Ingress protection rating | - | IP34 |
| Ingress protection rating of the drive | - | IP54 |

Dimensions

| L | W | H | H1 | S1 |
|--------|--------|--------|--------|--------|
| 64.80" | 59.06" | 18.90" | 13.78" | 23.62" |

