

BlauAIR CFP 2500

Suspended Energy Recovery Units | Counter or Cross Flow Core

- Sound pressure level LpA at 3 m: 39
- Heat exchanger type: Counter flow
- Heat exchanger material: Aluminum
- Supply filter: MERV13 (MERV8)
- Extract filter: MERV13 (MERV8)
- Sound-insulated casing
- Casing material: Aluzinc steel

	Unit of measurement	BlauAIR CFP 2500
Phases	-	1
Minimum supply voltage	V	200
Maximum supply voltage	V	240
Power supply frequency	Hz	50/60
Rated power	W	2x740
Maximum airflow	CFM	1470
Sound pressure level LpA at 3 m	dB(A)	39
Heat exchanger type	-	Counter flow
Heat exchanger material	-	Aluminum
Weight	lb	640
Supply filter	-	MERV13 (MERV8)
Extract filter	-	MERV13 (MERV8)
Transported air temperature (max)	°C	122
Transported air temperature (min)	°C	-31
Transported air temperature (max)	°F	251
Transported air temperature (min)	°F	-24
Ingress protection rating	-	IP34
Ingress protection rating of the drive	-	IP54

Dimensions

L	W	H	H1	S1
64.80”	59.06”	18.90”	13.78”	23.62”

