



BlauAIR RV 1200

Floor mounted heat recovery units

- Sound pressure level LpA at 3 m: 36
- Heat exchanger type: Rotary
- Sound insulation
- Motor type: EC
- Casing material: Aluzinc steel

| | Unit of measurement | BlauAIR RV 1200 |
|--|---------------------|-----------------|
| Phases | - | 1 |
| Minimum supply voltage | V | 200 |
| Maximum supply voltage | V | 240 |
| Power supply frequency | Hz | 50/60 |
| Rated power | W | 2x610 |
| Maximum airflow | m ³ /h | |
| Maximum performance @0.1" | CFM | 705 |
| Sound pressure level LpA at 3 m | dB(A) | 36 |
| Heat exchanger type | - | Rotary |
| Heat exchanger material | - | Aluminum |
| Weight | kg | 0 |
| Transported air temperature (max) | °C | 122 |
| Transported air temperature (min) | °C | -31 |
| Ambient air temperature min | °C | 0 |
| Ambient air temperature max | °C | 0 |
| Ingress protection rating | - | IP34 |
| Ingress protection rating of the drive | - | IP54 |

Dimensions

| L | W | H | H1 |
|--------|--------|--------|---------|
| 44.88" | 30.91" | 49.21" | Ø 9.84" |

