

BlauAIR RV 6000

Vertical Energy Recovery Units | Rotary Core

- Sound pressure level LpA at 3 m: 40
- Heat exchanger type: Rotary
- Heat exchanger material: Aluminum
- Supply filter: MERV13 (MERV8)
- Extract filter: MERV13 (MERV8)
- Sound-insulated casing
- Casing material: Aluzinc steel

	Unit of measurement	BlauAIR RV 6000
Phases	-	3
Minimum supply voltage	V	380
Maximum supply voltage	V	480
Power supply frequency	Hz	50/60
Rated power	W	2x2740
Maximum airflow	CFM	3500
Sound pressure level LpA at 3 m	dB(A)	40
Heat exchanger type	-	Rotary
Heat exchanger material	-	Aluminum
Weight	kg	715
Weight	lb	1576
Supply filter	-	MERV13 (MERV8)
Extract filter	-	MERV13 (MERV8)
Transported air temperature (max)	°C	122
Transported air temperature (min)	°C	-31
Transported air temperature (max)	°F	251
Transported air temperature (min)	°F	-24
Ingress protection rating	-	IP34
Ingress protection rating of the drive	-	IP54

Dimensions

L	W	H	H1	S1
75.20”	54.72”	82.28”	19.69”	39.37”

